


LO-SF-1G-ZX

1.25Gbps SFP 1550nm Optical Transceiver 80KM LC DDM

Product Features

- SFP package with LC connector
- 1550nm DFP laser and PIN photo detector
- Up to 80Km transmission on SMF
- +3.3V single power supply
- LVPECL compatible data input/output interface
- Low EMI and excellent ESD protection
- Laser safety standard IEC-60825 compliant
- Compatible with RoHS
- Digital Diagnostic SFF-8472 compliant
- Signal Ground Isolated to Case



Applications

- 1.25Gb/s 1000Base-LX Ethernet

Ordering information

Part Number	Product Description
LO-SF-1G-ZX	SFP 1.25Gbps ZX 1550nm LC DDM SMF 80km

Absolute Maximum Ratings

Parameter	Symbol	Minimum	Maximum	Units
Storage Temperature	Tst	-40	85	°C
Supply Voltage	Vcc	0	3.6	V
Operating Relative Humidity	RH	5	95	%

Recommended Operating Conditions

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Operating Case Temperature	Tc	0		70	°C
Supply Voltage	Vcc	3.15	3.3	3.45	V
Data Rate PER Channel	-	-	1.25	-	Gb/s

Transceiver Electrical Characteristics

Transmitter							
Parameter	Symbol	Minimum	Typical	Maximum	Unit	Notes	
Input Differential Impedance	Z _{IN}	90	100	110	Ω	-	
Differential Data Input Swing	V _{IN}	500	-	2400	mV	-	
TX_FAULT	Transmitter Fault	V _{OH}	2.0	-	V _{CCHOST}	V	-
	Normal Operation	V _{OL}	0	-	0.8	V	-
TX_DISABLE	Transmitter Disable	V _{IH}	2.0	-	V _{CCHOST}	V	-
	Transmitter Enable	V _{IL}	0	-	0.8	V	-
Receiver							
Parameter	Symbol	Minimum	Typical	Maximum	Unit	Notes	
Output Differential Impedance	Z ₀	-	100	-	Ω	-	
Differential Data Output Swing	V _{OUT}	370	-	2000	mV	-	
RX_LOS	Loss of signal (LOS)	V _{OH}	2.0	-	V _{CCHOST}	V	-
	Normal Operation	V _{OL}	0	-	0.8	V	-

Transmitter Optical Characteristics

Parameter	Symbol	Minimum	Typical	Maximum	Unit	Notes
Center Wavelength Range	λ_c	1540	1550	1560	nm	-
Spectral Width (RMS)	$\Delta\lambda$	-	-	1	nm	-
Extinction Ratio	ER	8	-	-	dB	-
Average Output Power	P_o	5	-	-2	dBm	-
Rise/Fall Time(20%-80%)	T_r/T_f	-	-	180	ps	-
Total jitter	T_j	-	-	0.43	UI	-
Optical Eye Diagram	IEEE 802.3z and ANSI Fibre Channel Compatible					

Receiver Optical Characteristics

Parameter	Symbol	Minimum	Typical	Maximum	Unit	Notes
Center Wavelength	λ_c	1260	-	1620	nm	-
Receiver Sensitivity	R_{sen}	-	-	-24	dBm	-
Receiver Overload	R_{ov}	-3	-	-	dBm	-
Optical Return Loss	ORL	12	-	-	dB	-
LOS De-Assert	LOS_D	-	-	-25	dBm	-
LOS Assert	LOS_A	-36	-	-	dBm	-
LOS Hysteresis	-	0.5	-	5	-	-

Mechanical specifications

